

Last modification 2021-09-01

KATO DL110-WH3C
9329501049785



Overview

Family name	Kato
Item Type	Downlight (DL)
Mounting	Recess

Color / Material

Glass Finish	Matte
---------------------	-------

Size

Fixture Diameter (cm)	11.3
Fixture Height (cm)	6.0
Cut Out	90

Specification

Voltage Input	240V
Wattage (max)	10
Wattage	10W
Globe Type	LED integrated SMD
Globe / Light Source qty	1
Globe / Light Source included	Yes
Lumens	850
Color Rendering	>84
Dimmable	Triac
Power Factor	>0.90
Surge Protection	Yes (1.5 Kva)
Control Gear Included	Yes-integrated
Insulation class	IC-4
IP rating	IP44
Approvals	AS/NZS 60598.1.2003
Assembly Required	No
Installation Required	Yes (by Licensed Electrician only)

All representations within this document are subject to copyright. ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.
NOTE : All images , descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.

Barcode

GTIN 9329501049785

Pricing

PRICE - RRP incGST 19.0

Image -dimensions



